

# PE SERIES EMERGENCY LIGHTING



The PE6 Series emergency egress fixture is designed to aesthetically match the P Series exit. With its high performance, adjustable optics, the six-volt unit is self-contained to provide 90 minutes of emergency lighting.



## Fixture Specifications

### FEATURES

- Compact, corrosion-resistant housing
- Two high-performance lamp heads present minimal intrusion into working space
- Regulated solid state charger constantly monitors the charge of the battery
- Low-voltage disconnect protects battery from deep discharge
- AC power indicator LED and test switch
- Optics include glare-reducing lens and tool-free adjustability
- Six-volt maintenance-free battery
- Damp location listed

### PE6 ORDERING INFORMATION

(use model designation as ordering number)

Catalog Number	DC Output		Fixture Load AC (amp)	Weight (without lamp heads or options)
	V	W		
<b>PE6</b>	6	12	.16	6 lb. 2 oz.
<b>PE6-25-2R61<sup>1</sup></b>	6	25	.10	7 lb. 10 oz.

<sup>1</sup> Two-head EM light with remote capability.

### PE6 ACCESSORIES

(Must be ordered separately)

Catalog Number	Description
<b>WG</b>	Wireguard
<b>PCS-1</b>	Polycarbonate shield


### R6 INDOOR/OUTDOOR REMOTE HEAD ORDERING INFORMATION

(use model designation as ordering number)

Catalog Number	Description
<b>A6H6A</b>	Remote Head, round, 5 watts, halogen, 6 volts, black
<b>MPWP1</b>	Black single-head mounting plate

Note: Consult factory for other remote mounting options.

### DIMENSIONS



A	B	C
13.25"	5.25"	3.625"
(337mm)	(133mm)	(92mm)



A6H6A/MPWP1



A HUBBELL LIGHTING, INC. COMPANY

Performance Designed Lighting Products

[www.securitylighting.com](http://www.securitylighting.com)

1085 Johnson Drive • Buffalo Grove, IL 60089 • TOLL-FREE: 800-544-4848 • PHONE: 847-279-0627 • FAX: 847-279-0642