

UCL



The UCL is an innovative, modular design consisting of a UCO1, 2 or 3 optical assembly and a UCB ballast unit. The multiple optics utilize the same ballast box assembly allowing you to change optics in the field. The canopy decking must be constructed of a non-combustible, flat material like aluminum or steel sheet metal (consult factory for other canopy construction prior to installation).


NOT SUITABLE FOR DOUBLE DECK CANOPY OR ENCLOSED CEILING APPLICATIONS.



Fixture Specifications

FEATURES

- Modular design.
- Die-cast construction for durability and efficient cooling.
- White Lekrocoate powder paint standard.
- Adjustable reflectors (UCO1).
- On-ground relamping with standard changers.
- Below-canopy installation capability.
- Glass - prismatic cut for UCO1 and UCO2, UCO3 is C73 patterned glass.
- Easy optical assembly replacement from below.
- Tool-free, hinged ballast cover.
- Tool-free, positive optical latching for reliable sealing.
- ED-28 lamp included.
- Self-centering optical hinges.
- Custom, field-adjustable cutoff shielding (UCO1).
- Pre-wired lamp socket.
- Complete UCL and canopy gasketing.
- Two 1/2" conduit holes for thru-wiring on ballast assembly.
- Two-box packaging for flexibility and convenience.
- Self-aligning installation.
- CSA and UL Listed for Wet Locations.



UCB Ballast Unit
14" L x 7.5" W x 5" H



ORDERING INFORMATION

SAMPLE CATALOG NUMBER

UCL **X** **XXX** **8** **WH** **L** **XXXXX**
Series Optical Pkg. Lamp/Watt. Voltage Color Lamp Options

SERIES

UCL = Under Canopy Lighting

OPTICAL PACKAGE

BLANK = Digit left blank when ordering UCO1
2 = UCO2 Optics - Sag Glass
3 = UCO3 Optics - Flat Glass

LAMP TYPE/WATTAGE

P10 100 watt pulse start metal halide
P15 150 watt pulse start metal halide
P17 175 watt pulse start metal halide
P25 250 watt pulse start metal halide
P32 320 watt pulse start metal halide
P35 350 watt pulse start metal halide
P40 400 watt pulse start metal halide

VOLTAGE

8 = Quad-Tap
5 = 480V
6 = Tri-Tap

COLOR

WH = White

LAMP

L = Lamp included (standard)

OPTIONS

Fuse
F1 = 120V
F2 = 208V
F3 = 240V
F4 = 277V
F5 = 480V
F6 = 347V

OPTIONS CONTINUED

UCK-1 Two Support Rails
UCL-HS Internal House-Side Shield (only available with UCL1 optic)
UCL-LC ED-28 Lamp Changer
UCL-CP 23" Square White Cover Panel
UCO1 White Replacement Optical Assembly
UCO2 White Replacement Optical Assembly
UCO3 White Replacement Optical Assembly

UCL-TEMPLATE

(order 1 free per standard canopy job; non-UCT retrofit installations)



Performance Designed Lighting Products

www.securitylighting.com

1085 Johnson Drive • Buffalo Grove, IL 60089 • TOLL-FREE: 800-544-4848 • PHONE: 847-279-0627 • FAX: 847-279-0642