

WALLWASH COMPACT FLUORESCENT



FEATURES

- Die cast and extruded aluminum housing, rotates 110° from horizontal, 358° in plan
- Connector has solid copper contact bars, fixed for one or two circuit connection without modification
- Two thermoplastic 2G11 sockets, one at each end of the housing, wired with 105°C wire in black or white silicone insulator sleeve
- Finished in stainless steel or baked enamel satin in black or white
- Electronic 2-lamp, .90 pf, electronic ballast standard, includes end-of-life protection circuit
- Fixture contains sponge rubber pads at housing ends to allow safe lamp removal




Fixture Specifications

ORDERING INFORMATION

Catalog Number	Description
AKTHLCE227WH	Compact Fluorescent Wallwash - two 24 / 26 / 27 watt - white
AKTHLCE227BL	Compact Fluorescent Wallwash - two 24 / 26 / 27 watt - black
AKTHLCE227Z	Compact Fluorescent Wallwash - two 24 / 26 / 27 watt - stainless steel
AKTHLCE240WH	Compact Fluorescent Wallwash - two 40 watt - white
AKTHLCE240BL	Compact Fluorescent Wallwash - two 40 watt - black
AKTHLCE240Z	Compact Fluorescent Wallwash - two 40 watt - stainless steel

DIMENSIONS



	A	B
AKTHLCE227	14.5"	7.375 - 8.5"
Compact Fluorescent Long Twin Tube T-5 12" 24, 26, or 27 watt		
AKTHLCE240	24.125"	7.375 - 8.5"
Compact Fluorescent Long Twin Tube T-5 40 watt		



A HUBBELL LIGHTING, INC. COMPANY

Performance Designed Lighting Products

www.securitylighting.com

1085 Johnson Drive • Buffalo Grove, IL 60089 • TOLL-FREE: 800-544-4848 • PHONE: 847-279-0627 • FAX: 847-279-0642